

Steriking® RS300 rotosealer

Reliable and easy to use sealing machine with integrated printer



Improved safety

- Equipped with sealing parameters (time, temperature, pressure) control and thus in compliance with ISO 11607-2.


Internal printer and connection to PC

- You can print one line of text which can consist of up to 30 characters, and it can also be connected with external label printer and PC.

Easy to clean and service

- Housing of the sealer is smooth and all corners are rounded for easy cleaning. The machine can be easily opened and serviced without the use any tools.

Steriking® RS300 rotosealer



Characteristics

Conformity to ISO 11607-2	X
Conformity to DIN 58953-7	X
Mains connection (100-120 V and 220-240 V)	X
Seal width & type	12 mm flat seal
Microprocessor controlled	X
Process parameters control	X
Automatic motor stop if machine not used	X
Stand-by function	X
Languages (in menu)	EN/ES/DE/IT/FR/NL/SV/DA/TR/FI
Temperature tolerance	±1 %
Sealing speed	10 m/min
Sealing temperature range	50°C-199°C
Sealing pressure	Self adjusting pressure
Internal printer	dot matrix
USB port	X
Power consumption (W), average & maximum	Max. 330 W
Dimensions	527x314x162 mm
Weight	15 Kg
Warranty period	24 months, 60 months for motor and fan
Technical/service manual	Available

We care that you pack safely!



Involve. Inspire. Impress.

www.steriking.com
e-mail: steriking@wipak.com

Wipak reserves right to make changes at any time without notice.